Exceptional service in the national interest



Obtaining Threading Performance Portability in SPARTA using Kokkos

Stan Moore

DOE COE Performance Portability Meeting

April 20, 2016







SPARTA




(Stochastic PArallel Rarefied-gas Time-accurate Analyzer)

- Direct Simulation Monte Carlo (DSMC) code
- Models rarefied gas flows using particles
- Features in situ meshing and visualization
- Core developers are Steve Plimpton and Michael Gallis (Sandia)
- Open-source, http://sparta.sandia.gov







SPARTA (cont.)



- Relatively new code—first public release in July 2014
- Written using object-oriented C++ (~45,000 lines)
- Parallelized using MPI and domain decomposition
- Easily extensible using C++ virtual inheritance—reduces code duplication
- No third-party libraries

Kokkos



(Greek for *kernel* or *grain*)

- Provides abstractions (in C++) for both parallel execution of code and data management
- Designed to target complex node architectures with N-level memory hierarchies and multiple types of execution resources
- Currently can use OpenMP, Pthreads, and CUDA as backend programming models
- Core developers are Carter Edwards and Christian Trott (Sandia)
- Open-source, <a href="https://github.com/kokkos/ko

Kokkos (cont.)



- In practice, Kokkos allows SPARTA to:
 - Use threading on top of existing MPI parallelization (MPI + X)
 - Run and give reasonable performance on multithreaded CPUs, Xeon Phis, and GPUs
- Kokkos abstractions only require a single C++ code base

Initial Porting Strategy



- Leverage (reuse) the original SPARTA code instead of a complete rewrite
- Keep the Kokkos version as similar to the original MPI code as possible
- Initially parallelize kernels using simple parallel loops (no thread teams)
- Find and optimize bottleneck kernels, adding more complexity to the Kokkos code if necessary (ongoing)

"Premature optimization is the root of all evil" - Donald Knuth

Initial Porting Strategy (cont.)



- Kokkos package is an optional add-on to SPARTA
- Uses C++ virtual inheritance and functions to reduce code duplication
- First such optional package in SPARTA
- Patterned after the LAMMPS molecular dynamics code, which has 61 optional packages (including a similar Kokkos package)
- So far, particle moves without complex surfaces have been ported, along with the collide routine

Kokkos Porting Workflow



- 1. Profile code to find bottlenecks
- 2. Identify a kernel to be threaded (in SPARTA: typically loops over particles or grid elements)
- 3. Change kernel data structures to Kokkos *views*
- 4. Change kernel loop to Kokkos *parallel for, reduce,* or *scan*
- Make changes, if necessary, to ensure the kernel is threadsafe (modify kernel or use atomics)
- 6. Test code on CPU/Xeon Phi
- 7. Add in memory transfer between host and device
- 8. Test code on GPU

Incremental Approach




- Kokkos dual views contain a reference to data in device (e.g. GPU) memory as well as a mirror copy on the host (e.g. CPU)
- Can easily sync between host and device copies
- Non-Kokkos code runs on the host
- SPARTA uses primitive memory allocation (no std::vector)
- Data structures are allocated using Kokkos, and pointers to the data structures in non-Kokkos code are set to point to the Kokkos host view
- This allows non-Kokkos portions of the code to still run with zero or little modification (may need some memory transfer for GPU)

Results



- Collisional benchmark with 10 million particles for strong scaling
- Used 1 MPI task (1 Sandy Bridge CPU) per K20X GPU



Challenges—Code Maintenance



- Since Kokkos threading package is an optional add-on to SPARTA, need to prevent divergence between original MPI and Kokkos code versions
- Must periodically synchronize changes and bug fixes
- Regression testing can help catch changes to main SPARTA that break the Kokkos package
- Without Kokkos, would still need a CUDA version and an OpenMP version of SPARTA

Challenges—Specialization



Case study: atomics

- Statistics, such as number of collisions, number of cell crossings, etc. are collected inside thread parallel loops
- For thread safety, can either use a parallel reduction over threads or an atomic fetch-and-add to global variables
- On K20X GPU, atomics are 10% faster than parallel reduction (overall for a collisional benchmark problem)
- On BGQ, atomics are 7% slower than parallel reduction
- How much code complexity is a 10% gain in performance worth? (However, little differences add up)
- Chosen solution: add command line option to toggle between parallel reduction and atomics

Conclusions



- Using Kokkos in SPARTA gives reasonable threading performance on multiple platforms
- Kokkos allows one to leverage existing C++ code—a complete rewrite isn't necessary and an incremental porting approach is possible
- Some code specialization for different platforms will probably always be necessary to gain maximum performance

Questions?

